

Concrete Tank Data Sheet

SIZE (Gallons)	DIMENSIONS	BOTTOM OF TANK TO CENTRE TO INLET	OVERALL HEIGHT	BOTTOM OF TANK TO CENTRE OF OUTLET	WEIGHT (LBS)	WORKING CAPACITY OF 1st COMPARTMENT (Gallons)	VOLUME OF 2nd COMPARTMENT (Gallons)	TOTAL VOLUME AS A HOLDING TANK LOAD (Gallons)
850 Septic Tank	64½" x 98½"	57"	65½"	37"	11 300	650	208	993
1000 Septic Tank	72" x 100"	57"	65½"	37"	13 000	752	223	1160
1250 Septic Tank	79" x 103"	63"	72"	43"	14 200	956	292	1 427
500 Holding Tank	50¼" x 74¼"	56¼"	64 ¾"	54½"	6 000	500		
250 Sump (2 compartments)	2' 10" x 5' 2"		3' 10"		3 700			250

Manhole Extensions (36" outside dia.) come in 1', 1½', 2', 3', and 5' Sections

Concrete Precast - sulphate resistant NEW type 50 concrete with Fibre Mesh at 45 mpa strength after 28 day.

Septic Tanks c/w 4" ABS rubber coupler for inlet & 2" ABS Rubber Coupler Outlet

Siphon Tanks c/w 2" to 4" ABS couplers for outlets.

Water Cisterns c/w 1¼" PVC threaded couplers inside and out.

Holding Tanks are 4" Rubber Coupler Inlet & 4" Rubber Coupler Outlet for Expansion of System

All Tanks come with a 36" Insulated Lid.

Effective April 1, 2017